

Literature

Reviews

Ferroelectric properties of vinylidene fluoride copolymers - Takeo Furukawa; *Phase Transitions*. **1989**, DOI: [10.1080/01411598908206863](https://doi.org/10.1080/01411598908206863)

Novel polymer ferroelectric behavior via crystal isomorphism and the nanoconfinement effect - Lianyun Yang, Xinyu Li, Elshad Allahyarov, Philip L. Taylor, Q.M. Zhang, Lei Zhu; *Polymer*. **2013**, DOI: [10.1016/j.polymer.2013.01.035](https://doi.org/10.1016/j.polymer.2013.01.035)

Vinylidene fluoride- and trifluoroethylene-containing fluorinated electroactive copolymers. How does chemistry impact properties? - Thibaut Soulestin, Vincent Fabrice, Domingues Dos Santos, Bruno Améduri; *Prog. Polym. Sci.* **2017**, DOI: [10.1016/j.progpolymsci.2017.04.004](https://doi.org/10.1016/j.progpolymsci.2017.04.004)

Recent Progress in the Development of Printed Thin-Film Transistors and Circuits with High-Resolution Printing Technology - Kenjiro Fukuda and Takao Someya; *Adv. Mater.* **2016**, DOI: [10.1002/adma.201602736](https://doi.org/10.1002/adma.201602736)

PVDF-Based Ferroelectric Polymers in Modern Flexible Electronics - Xin Chen, Xu Han, and Qun-Dong Shen; *Adv. Electron. Mater.* **2017**, DOI: [10.1002/aelm.201600460](https://doi.org/10.1002/aelm.201600460)

Key Articles on VDF- and TrFE Based Copolymers

Ferroelectric Polymers - Andrew J. Lovinger; *Science*. **1983**, DOI: [10.1126/science.220.4602.1115](https://doi.org/10.1126/science.220.4602.1115)

Giant Electrostriction and Relaxor Ferroelectric Behavior in Electron-Irradiated Poly(vinylidene fluoride-trifluoroethylene) Copolymer - Q. M. Zhang, Vivek Bharti, X. Zhao; *Science*. **1998**, DOI: [10.1126/science.280.5372.2101](https://doi.org/10.1126/science.280.5372.2101)

Large Electrocaloric Effect in Ferroelectric Polymers Near Room Temperature - Bret Neese, Baojin Chu, Sheng- Guo Lu, Yong Wang, E. Furman, Q. M. Zhang; *Science*. **2008**, DOI: [10.1126/science.1159655](https://doi.org/10.1126/science.1159655)

The negative piezoelectric effect of the ferroelectric polymer poly(vinylidene fluoride) - Ilias Katsouras, Kamal Asadi, Mengyuan Li, Tim B. van Driel, Kasper S. Kjær, Dong Zhao, Thomas Lenz, Yun Gu, Paul W. M. Blom, Dragan Damjanovic, Martin M. Nielsen and Dago M. de Leeuw; *Nature Materials*. **2015**, DOI: [10.1038/nmat4423](https://doi.org/10.1038/nmat4423)

Selection of Research Articles using Piezotech Polymers

Varifocal liquid-filled microlens operated by an electroactive polymer actuator - Seung Tae Choi, Jeong Yub Lee, Jong Oh Kwon, Seungwan Lee, Woonbae Kim; *Opt. Letters*. **2011**, DOI: [10.1364/OL.36.001920](https://doi.org/10.1364/OL.36.001920)

Relaxor Ferroelectric Behavior from Strong Physical Pinning in a Poly(vinylidene fluoride-co-trifluoroethylene-co-chlorotrifluoroethylene) Random Terpolymer - Lianyun Yang, Brady A. Tyburski, Fabrice Domingues Dos Santos, Maya K. Endoh, Tadanori Koga, Daniel Huang, Yijun Wang, and Lei Zhu; *Macromolecules*. **2014**, DOI: [10.1021/ma501852x](https://doi.org/10.1021/ma501852x)

Impact of crystallization on ferro-, piezo- and pyro-electric characteristics in thin film P(VDF-TrFE) - A. Aliane, M. Benwadih, B. Bouthinon, R. Coppard, F. Domingues Dos Santos, A. Daami; *Org. Electronics*. **2015**, DOI: [10.1016/j.orgel.2015.06.007](https://doi.org/10.1016/j.orgel.2015.06.007)

From solvent-cast to annealed and poled poly(VDF-co-TrFE) films: New insights on the defective ferroelectric phase - François Bargain, Pierre Panine, Fabrice Domingues Dos Santos, Sylvie Tencé-Girault; *Polymer*. **2016**, DOI: [10.1016/j.polymer.2016.10.010](https://doi.org/10.1016/j.polymer.2016.10.010)

Enhanced electromechanical performances in plasticizer modified electrostrictive polymers - Xunqian Yin, Qing Liu, Jérémy Galigneau, Pierre-Jean Cottinet, Daniel Guyomar, Jean-Fabien Capsal; *Euro. Polym. J.* **2016**, DOI: [10.1016/j.eurpolymj.2016.01.030](https://doi.org/10.1016/j.eurpolymj.2016.01.030)

Optimization Of PVDF-TrFE Processing Conditions For The Fabrication Of Organic MEMS Resonators - Pierre-Henri Ducrot, Isabelle Dufour, Cédric Ayela; *Sci. Reports*. **2016**, DOI: [10.1038/srep19426](https://doi.org/10.1038/srep19426)

Mechanical strain induced changes in electrical characteristics of flexible, non-volatile ferroelectric OFET based memory - Damien Thuau, Mamatimin Abbas, Guillaume Wantz, Lionel Hirsch, Isabelle Dufour, Cédric Ayela; *Org. Electronics*. **2017**, DOI: [10.1016/j.orgel.2016.10.036](https://doi.org/10.1016/j.orgel.2016.10.036)

Semicrystalline Organization of VDF- and TrFE-Based Electroactive Terpolymers: Impact of the trans-1,3,3,3-Tetrafluoropropene Termonomer - François Bargain, Thibaut Soulestin, Fabrice Domingues Dos Santos, Vincent Ladmiral, Bruno Améduri, and Sylvie Tencé-Girault; *Macromolecules*. **2017**, DOI: [10.1021/acs.macromol.7b00051](https://doi.org/10.1021/acs.macromol.7b00051)

Contact Information

Piezotech
Arkema-CRRA
Rue Henri Moissan
69496 Pierre-Benite Cedex
FRANCE

Info.piezotech@arkema.com
Phone: +33 4 72 39 87 03
www.piezotech.eu

Disclaimer: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.